



SIZE: 1200mm x 1000mm

- 1 Ensure all blocks and panels are free of dust and loose particles.
- 2 Apply a flexible waterproof membrane to the bottom of 7 blocks, which will form the first course ensuring coverage is extended at least 60mm up all edges. Allow to dry.
- 3 Mark a rectangle on the slab: 1200mm long x 1000mm wide or design the slab to these dimensions.
- 4 Lay Hebel® Mortar on the slab to assist in getting the first course of blocks straight and level.
- 5 Lay the first course of blocks within the setout lines, leaving a 400mm opening at the front for access, ensuring all vertical joints are glued together using Hebel® Adhesive.
- 6 Apply Hebel® Adhesive between each course and lay the second and third courses in stretcher bond ensuring the blocks overlap each other by 100mm minimum.
- 7 Apply Hebel® Adhesive and lay the fourth course complete with no opening. The block above the opening is a full block and must have 100mm bearing on the blocks below.
- 8 To create a sloping roof mark 50mm down from the top of the fourth course at each end and mark a line. Across the front and rear of the Kennel mark a line flush with the high side down to the 50mm mark.
- 9 Cut the individual blocks on the angle marked.
- 10 Apply Hebel® Adhesive to the top of the blocks.
- 11 Place the Hebel® Handi panels on top of the Kennel making sure they overhang equally on each side.
- 12 Insert 4 x 150mm bugle head batten screws to each panel ensuring they enter the centre of the block below.
- 13 Allow to dry.
- 14 The Dog Kennel is now ready for the coating system.



COATING

BASECOAT - Hebel® HighBuild

Specially formulated for the Hebel® substrate (standard cement renders are not recommended). Provides a base levelling and preparation coat for subsequent acrylic texture coating systems.

TEXTURE FINISH options:

Dulux® Fine Texture - Provides a uniform sandy texture, applied with a normal paint roller.

Dulux® Medium Texture - Provides a bagged style texture finish for a character Tuscan appearance. **Dulux® Full Cover Texture** - Provides a crisp "monolithic" feature finish.

WEATHER PROOFING: Dulux® WeatherShield X10 - Premium exterior acrylic, providing ultimate weathering resistance.

SHOPPING LIST

- Flexible waterproof membrane
- 26 x 100mm Hebel® Blocks
- 2 x 1200mm Hebel® Panels
- 1 x 20kg bag of Hebel® Mortar
- 1 x 20kg bag of Hebel® Adhesive
- 8 x bugle head batten screws
- Mixing bucket

TOOLS REQUIRED

- Stirrer for electric drill
- Hex driver for batten screws
- Trowel for render (unless a sponged finish is required)
- 1200mm level

SAFETY INFORMATION

As with all cementitious products, the user should take all precautions associated with cutting concrete. These precautions include: P1 or P2 class respirators (for fine dust from powered cutting tools), eye protection and ear protection, as well as long sleeved clothes and gloves, as dust could irritate the skin. Hebel® recommends reading all relevant Material Safety Data Sheets (MSDS) prior to working with Hebel® products. MSDS's can be downloaded from the Hebel® website www.hebelaustralia.com.au

HANDY TIP

First cut and dry stack your project without Hebel® Adhesive to ensure the project is correct. Then you can glue the project together with confidence.

For more ideas on Hebel® DIY projects visit:
www.hebelaustralia.com.au



HEB - 2006
Environmentally Innovative Products

CSR